

NAAWS 3.1 Errata

Section	Page Number	Item Number	Errata Change	Reference Number	Effective Date
Intro	3	AWMAC	Change address/phone to: PO Box 36525, RPO MacTaggart Edmonton, AB T6R 0T4 403-981-7300		07/16/18
Preface	20	Center Paragraph	Remove fourth paragraph starting with: "NAAWS is offered in two . . ."	2049	07/17/17
Preface	22	Left Column Header	Change header text from " NORTH AMERICAN ARCHITECTURAL WOODWORK STANDARDS " to " DIMENSIONAL CHANGE IN ARCHITECTURAL MILLWORK "	2088	01/01/18
01	33	1.4.4.5.1	Remove duplicate Item 1.4.4.5.1 located approximately 1/3 rd down the left-hand column.	2027 & 2047	07/17/17
01	33	1.4.4.5.1.8	Correct text to read: Solid phenolic. core.	2096	01/01/18
01	33	1.4.4.6.1.1	Correct text to read: "1/4" = 1'-0" (1:50 metric)"		07/17/17
01	33	1.4.4.6.1.2	Correct text to read: "3/8" = 1'-0" (1:20 metric)"		07/17/17
01	33	1.4.4.6.1.3	Correct text to read: "1-1/2" = 1'-0" (1:10 metric)"		07/17/17
01	33	1.4.4.6.1.4	Correct text to read: "3" = 1'-0" (1:5 metric)"		07/17/17
01	34	1.4.5.1.2.1	Remove the text "(1:1)".		07/17/17
01	34	1.4.5.1.2.1.1	Remove the text ", 1:2 ratio".		07/17/17
01	34	1.4.5.1.2.2	Remove the text: "drawn to a minimum 3" = 1'-0" (1:5) scale"		07/17/17
01	35	1.4.5.1.2.5	Correct text to read: "1-1/2" = 1'-0" (1:10 metric)"		07/17/17
01	35	1.4.5.1.2.5.1	Correct text to read: "3" = 1'-0" (1:5 metric)"		07/17/17
01	35	1.4.5.1.2.6	Remove the text: ", minimum 1-1/2" = 1'-0" (1:10) scale,"		07/17/17
01	35	1.4.5.2.2.4	Remove the text: ", minimum 1-1/2" = 1'-0" (1:10) scale,"		07/17/17
01	36	1.4.5.4.2.3	Remove the text: ", minimum 1-1/2" = 1'-0" (1:10) scale,"		07/17/17
01	37	1.4.5.5.2.3	Add new Item 1.4.5.5.2.3.14 to read: " Shelf core, thickness and load rating. "	2048	07/17/17
01	37	1.4.5.5.2.3	Correct d text to read: "1/2" = 1'-0" (1:30 metric)"		07/17/17
01	37	1.4.5.6.2.5	Correct text to read: "3" = 1'-0" (1:5 metric)"		07/17/17
01	38	1.4.5.7.4.4	Remove the text: "in minimum 1-1/2" = 1'-0" (1:10) scale,"		07/17/17
03	57	Right-hand Column	At FIR, DOUGLAS heading, remove the text "cut edge" and replace with " edge cut ".	2043	07/17/17

NAAWS 3.1 Errata

Section	Page Number	Item Number	Errata Change	Reference Number	Effective Date
04	121	4.4.13	Change incorrect ASTM D120-37-12 reference to “ASTM D 1037-12”	2074	01/01/18
04	121	4.4.14	Change incorrect ASTM D120-37-12 reference to “ASTM D 1037-12”	2074	01/01/18
05	144	5.5.1.2.5	Correct text to read: “. . . (decorative laminate, Solid Phenolic and panel products).” By adding comma.	2095	01/01/18
06	167	6.4.5.1.1	Change text “finish” to “finished”.	2045	07/17/17
06	185	6.7.1.2.5	Correct text to read: “. . . (decorative laminate, Solid Phenolic and panel products).’ By adding comma.	2095	01/01/18
07	208	7.7.1.2.5	Correct text to read: “. . . (decorative laminate, Solid Phenolic and panel products).’ By adding comma.	2095	01/01/18
08	224	Figure 8-014	Remove “Figure: 8-014” and text: “For durability, the bottom edge of wall surfacing is edgebanded.”	2094	01/01/18
08	234	8.2.1	Change text to read: “. . . solid phenolic composite and solid . . . “	2097	01/01/18
08	249	8.4.7.D.2.1	Correct spelling of “aluminium,” to “aluminum”	2089	01/01/18
08	257	8.7.1.2.5	Correct text to read: “. . . (decorative laminate, Solid Phenolic and panel products).’ By adding comma.	2095	01/01/18
09	298	9.6.4.15.1.2	Change to read: “An additional hinge for each additional 30” (762 mm) or portion thereof in door height.”	2100	01/01/18
09	298	9.6.4.15.1.2.1	Remove this Item in its entirety.	2100	01/01/18
09	300	9.7.1.2.5	Correct text to read: “. . . (decorative laminate, Solid Phenolic and panel products).’ By adding comma.	2095	01/01/18
10	306	Center Column	At LABORATORY CASEWORK heading, 2 nd paragraph, remove duplicate text “s intended to assist design professionals in”.	2026	07/17/17
10	322	10.3.1	Change text to read: “. . . non premium priced standard non-directional pattern, color, . . .”	2073	01/01/18
10	322	10.3.1.1	Add new Item 10.3.1.1.2 reading: “ Solid Phenolic casework shall be Premium Grade. ”	2098	01/01/18
10	332	10.4.7.8.7	Add new Item 10.4.7.8.7.2 to read: “ Combination cores are not guaranteed against warping. ”	2036	07/17/17

NAAWS 3.1 Errata

Section	Page Number	Item Number	Errata Change	Reference Number	Effective Date
10	337	10.4.7.12.2	Correct Dimension to: “. . . ¼” (6.4 mm) . . .”	2099	01/01/18
10	339	10.4.7.16.10.1.5.2	At FRENCH version only, change Item number to read: “ 10.4.7.17.10.1.5.2 ”	2029	07/17/17
10	340-346	10.4.7.16.9 . . .	Correct Item numbering to” “ 10.4.7.17.10 . . . ”	2030 & 2027	07/17/17
10	347	10.4.7.22.3.1.2	Change Text to read: “Exposed fasteners are not permitted at exposed exterior surfaces, except: ” and add bullets for C & P.	2069	01/01/18
10	347	10.4.7.22.3.1.2	Add new Item 10.4.7.22.3.1.2.1 reading: “ At access panels. ”	2069	01/01/18
10	347	10.4.7.22.3.1.3.2	Omit entirely.	2069	01/01/18
10	347	10.4.7.22.3.1.6.4	Correct Dimension to: “ 5” (127 mm) . . . ”	2129	11/07/18
10	349	10.4.7.22.4	Correct text to read: “. . . been independently (Federal or Provincial/State regulated university, collage or technical (post high school) school, or licensed testing facility) tested . . .”	2022	07/17/17
10	349	10.4.7.22.8.3	Move illustration overlaid on this page text to Item 10.4.7.23.8.3.	2061	07/17/17
10	356	10.4.5.B.2.4.1	Correct text to read: “. . . as the face and color, grain, or pattern match to Semi-exposed Surface. ”	2032	07/17/17
10	358	10.4.5.C	Change red header text to read: “ Applicable to Premium Grade Only ”	2090	01/01/18
10	358	10.4.7.C	Change red header text to read: “ Applicable to Premium Grade Only ”	2090	01/01/18
10	359	10.1.D.3.3	Change Item to read: “ Countertops (work surfaces) ”	2101 & 2102	01/01/18
10	360	10.4.4.D.1.4	Change Item to read: “ MECHANICAL CHASE ACCESS and CLOSURE PANELS at all base and peninsula cabinets, including drawer banks, and shall.”	2103	01/01/18
10	360	10.4.4.D.1.4.1	Change Item to read: “ Be neatly cut within the back ”	2103	01/01/18
10	360	10.4.4.D.1.4.2	Change Item to read: “ Be as large as practical without interfering with installation requirements.”	2103	01/01/18
10	360	10.4.4.D.1.4	Add new Item 10.4.4.D.4.3 reading: “ Have removable closure panels, except: ”	2103	01/01/18
10	360	10.4.4.D.1.4	Add new Item 10.4.4.D.4.3.1 reading: “ At full height drawer bank cabinets. ”	2103	01/01/18
10	362	10.6.4.5.4.4	Change Text to read: “Exposed fasteners at exposed exterior surfaces, except: ” and add bullets for C & P.	2069	01/01/18

NAAWS 3.1 Errata

Section	Page Number	Item Number	Errata Change	Reference Number	Effective Date
10	362	10.6.4.5.4.4	Add new Item 10.6.4.5.4.4.1 reading: “At access panels.”	2069	01/01/18
10	364	10.6.4.10.2	Add new Item 10.6.4.10.2.3 to read: “Scribe ALLOWANCE shall not exceed 1-1/2” (38.1 mm) in width from cabinet body”.	2035	07/17/17
10	364	10.6.4.10.2	Add new Item 10.6.4.10.2.4 to read: “Where scribing is required at both ends of a cabinet run, it shall utilize the same type of scribing at each end and be uniform in scribing width not to exceed 20% in variance.”	2034	07/17/17
10	364	10.6.4.10.2.2.3	Change text to read: “Are NOT ALLOWED”.	2054	07/17/17
10	365	10.6.4.12	Omit entirely	2069	01/01/18
10	365	10.6.4.12.1	Omit entirely	2069	01/01/18
10	372	10.6.4.E.4.3.2	Change “18” (610 mm)” to read: “18” (457 mm)”	2122	07/16/18
10	376	10.7.1.3.1	Relocated the “!” icon to Item 10.7.1.3.1.	2028	07/17/17
10	376	10.7.1.2.5	Correct text to read: “. . . (decorative laminate, Solid Phenolic and panel products).’ By adding comma.	2095	01/01/18
11	402	11.4.5.B.1	Change text to read: “. . . a minimum of .039” (0.99 mm) plus/minus 0.005” (0.127 MM) in accordance with NEMA-LD3 (Latest edition), http://nema.org , in thickness . . .”	2023	07/17/17
11	402	11.4.5.B	Add new Item: 11.4.5.B.4 reading: “Grained or patterned selections that require seams, shall be well matched within the limits of the grain or pattern selection.” with bullets for C & P.	2093	01/01/18
11	409	11.4.7.E.5	Change text to read: “CANTILEVERED OVERHANGS with sub-top support, such as, (image), shall not exceed 6” (152 mm) for 3/4” (19 mm) thick, 12” (305 mm) for 1” (25.4 mm) thick or 16” (406 mm) for 1-1/4” (31.8 mm) material thickness whether in the front, back, or end.	2092	01/01/18
11	411	11.4.7.F.8	Change text to read: “CANTILEVERED OVERHANGS with sub-top support, such as, (image) shall not exceed 6” (152 mm) for 2 cm (13/16” (20 mm)) thick material or 10” (254 mm) for 3 cm (1-1/8” (28.6 mm)) material thickness, whether in the front, back, or end.	2092	01/01/18

NAAWS 3.1 Errata

Section	Page Number	Item Number	Errata Change	Reference Number	Effective Date
11	416	11.6.4.19.1	Change text to read: "Cutouts in HPDL shall have a minimum 1/4" (6.4 mm) radius at inside corners."	2070	01/01/18
11	419	11.6.4.25	Change Item numbering to: "11.6.4.27" including all subsequent sub items.	2091	01/01/18
11	419	11.6.4.27.3	Change text to read: "CANTILEVERED OVERHANGS with or without a sub-top, shall not exceed:	2092	01/01/18
11	419	11.6.4.27.3	Add new Item 11.6.4.27.3.1 reading: "For EPOXY RESIN: 6" (152 mm) for 3/4" (19 mm) thick, 12" (305 mm) for 1" (25.4 mm) thick or 16" (406 mm) for 1-1/4" (31.8 mm) material thickness, whether in the front, back, or end.	2092	01/01/18
11	419	11.6.4.25.3	Add new Item 11.6.4.27.3.2 reading: "For NATURAL/ENGINEERED STONE: 6" (152 mm) for 2 cm (13/16" (20 mm)) thick material or 10" (254 mm) for 3 cm (1-1/8" (28.6 mm)) material thickness, whether in the front, back, or end.	2092	01/01/18
11	420	11.7.1.2.5	Correct text to read: ". . . (decorative laminate, Solid Phenolic and panel products).' By adding comma.	2095	01/01/18
Appendix	435	Reference Source Listings	Change address/phone to: PO Box 36525, RPO MacTaggart Edmonton, AB T6R 0T4 403-981-7300		07/16/18
Appendix	438	Adhesive Usage Guidelines	At BASIC REQUIREMENTS , under "When intended for:" add new bulleted text line to read: " CLIMATE CONTROLLED USE DRY AREAS, water resistance is not required. "	2051	07/17/17
Appendix	438	Adhesive Usage Guidelines	At TYPE I FULLY WATER PROOF (Exterior) header, , add new line to read: " Polyurethane Reactive " with same properties as Epoxy and characteristics of: " Minimizes visible glue line. "	2051	07/17/17
Appendix	438	Adhesive Usage Guidelines	At TYPE I FULLY WATER PROOF (Exterior) header, under PVA, change additional text to read: ". . . Acetate Proprietary)"	2051	07/17/17
Appendix	438	Adhesive Usage Guidelines	At TYPE II WATER RESISTANT (Interior) , header, remove the line for PVC (Polyvinyl Chloride) adhesive.	2051	07/17/17
Appendix	438	Adhesive Usage Guidelines	At TYPE II WATER RESISTANT (Interior) , add new line to read: " PVA (Polyvinyl Acetate Crosslinked) " with properties matching those of Urea Resin and the characteristics of: Dries almost clear.	2051	07/17/17

NAAWS 3.1 Errata

Section	Page Number	Item Number	Errata Change	Reference Number	Effective Date
Appendix	438	Adhesive Usage Guidelines	Add new " NOT WATER RESISTANT (Interior) " header.	2051	07/17/17
Appendix	438	Adhesive Usage Guidelines	Below NOT WATER RESISTANT (Interior) header add new line for " PVA (Polyvinyl Acetate) " with same properties as Urea Resin and characteristics of: Carpenter's Glue – White.	2051	07/17/17
Appendix	438	Adhesive Usage Guidelines	Below NON WATER RESISTANT (Interior) header add new line for " Aliphatic Resin " with same properties as Urea Resin and characteristics of: Carpenter's Glue – Grey, Brown or Yellow.	2051	07/17/17
Appendix	438	Adhesive Usage Guidelines	;At foot notes, change first note to read: ". . . possible Type I & Type II rating."	2051	07/17/17
Appendix	447	Casework Integrity	At STRUCTURAL INTEGRITY TEST – WALL CABINET, PROCEDURE , change text to read: ". . . load the cabinet bottom, shelf, and top uniformly to 200 lbs. (90.7 kg) each, maximum total cabinet load shall not exceed 600 lbs. (272 kg)."		07/17/17
Rear Cover			Correct spelling of: "GLOSSARY"		07/16/18